

NEC MultiSync® EA192M

NEC LCD 19" Commercial Enterprise Displays

The EA192M is an energy saving 19" 5:4 format monitor. It offers LED backlight, DisplayPort connectivity and full adjustability. Low power consumption and low operating costs make the display perfect for use in the professional office environment. Outstanding ergonomic qualities and intelligent features such as the Ambient Light Sensor make it very user-friendly and help to increase productivity. Ideal for large corporates and medium sized businesses for the standard office use with environmental attention.



DELIVERING GENUINE BENEFITS

Image display - 19inch 5:4 TN with LED backlight.

Input - Display can be used with two digital (DVI-D, DisplayPort) and one analogue input.

Ambient Light Sensor - with Auto Brightness function always sets optimised brightness level according to ambient light and content conditions.

Vesa Mount (100 mm) - allows to install the monitor via various mounting solutions, stand has a quick release for faster installations.

Ergonomic Office - full height adjustability (110 mm), swivel, tilt and pivot functionality ensures perfect individual ergonomic set-

 $\begin{tabular}{ll} \textbf{Sustainable Office -} low power consumption with LED backlight and ambient light sensor. \end{tabular}$

Green Product Concept - Eco Mode and Carbon Footprint Meter, Ambient Light Sensor.

OUTSTANDING PERFORMANCE

- EA192M sets new standard in environmental compatibility. The Ambient Light
 Sensor serves to increase energy saving even further. It measures the ambient light
 and adjusts the screen to the optimum brightness automatically without any manual
 settings being required. The use of recycling plastic for the monitor housing and of
 mercury-free materials fulfil the demands of the "NEC Green Vision" campaign.
- The connection options ensure leading-edge compatibility. With a DisplayPort, a
 DVI-D as well as an analogue interface, the NEC MultiSync® EA192M provides
 outstanding connectivity and the optimum basis for all business applications. The
 display also features speakers and a headphone socket for comfortable office
 communication.
- Height adjustment through up to 110 mm and the pivot function allow the screen to be positioned to meet individual needs and ensure a high degree of userfriendliness. Thanks to its ergonomic and ecological characteristics, the monitor has gained TCO 5.0 certification and been awarded the EPEAT Silver Seal.
- The eco-friendly display EA192M further extends our comprehensive range for the
 corporate secotr. It helps to reduce running costs throughout the display's entire
 lifetime and ist features make daily operations simpler and more productive.
 Excellent value for money.



SPECIAL CHARACTERISTICS

Ambient light sensor for optimized brightness levels; Carbon Footprint Meter; Carbon Savings Meter; NaViSet®and NaViSet®Administrator compatible; sRGB Support; TORO™ Design; Windows 7 compatible; WindowsVistaCertifiedLogo



Panel Technology	W-LED TN TFT
Screen Size [inch/cm]	19.0 / 48.2
Screen Aspect Ratio	5:4
Pixel Pitch [mm]	0.294
Brightness (typ.) [cd/m²]	250
Contrast Ratio (typ.)	1000:1
Viewing Angle [°]	178 horizontal / 178 vertical (typ. at contrast ratio 5:1); 160 horizont / 160 vertical (typ. at contrast ratio 10:1)
Response Time (typ.) [ms]	4
Colours [Mio.]	16.77
SYNCHRONISATION RATE	
Horizontal Frequency [kHz]	30 - 82
Vertical Frequency [Hz]	56.0 - 75.0
RESOLUTION	
	1690 v 1050 ot 60 Hz
Optimum Resolution	1680 x 1050 at 60 Hz
Supported	800 x 600; 720 x 400; 640 x 480; 1152 x 864; 1024 x 768; 1152 x 870; 832 x 624
CONNECTIVITY	
Digital:	1 x DVI-D (with HDCP); 1 x DisplayPort
Analog:	1 x mini D-sub 15 pin
ELECTRICAL	
Power Consumption on Mode [W]	25 (typ.); 41 (max.); 18.0 (Eco Mode 1)
Power Savings Mode [W]	< 0.5
Power Supply	100-120 V/220-240 V; 1.0 A/0.5 A; integrated power supply
ENVIRONMENTAL CONDITIONS	100-120 V/220-240 V, 1.0 A/0.3 A, integrated power supply
	5.4 . 95
Operating Temperature [°C]	+5 to +35
Operating Humidity [%]	20 to 80
ERGONOMICS	
Height adjustable Stand [mm]	110
Screen Tilt [°]	-5 to 15
Screen Tilt / Swivel [°]	-45 to 45
Screen Rotate [°]	0 to 90 (landscape to portrait mode)
MECHANICAL	
Bezel Width [mm]	15.0
Dimensions (W x H x D) [mm]	408.0 x 386.4 x 213.9; Without stand: 408.0 x 338.0 x 65.0
Weight [kg]	5.5; Without stand: 4.6
VESA Mounting [mm]	100 x 100
ADDITIONAL FEATURES	
Colour Versions	Silver Front Bezel; White Back Cabinet; Black Front Bezel, Black Back Cabinet
Cable Management	yes
Kensington security slot	yes
Plug and Play	VESA DDC/CI; DDC2B/2Bi; EDID Standard
Audio	1W + 1W (De-activateable)
Adjust Functions	Auto Adjust; Colour Temperature Control; Fine Adjust (analog);
Aujust i uncaons	Brightness; Intelligent Power Management; Contrast; Monitor Information; sRGB; On-Screen-Display (OSD) lock-out; NTAA (Non Touch-Auto-Adjustment); Language Select; LED Brightness; Audio Volume / Lock-Out; EcoMode; Power-Off Timer; DV Mode
Shipping Content	Signal Cable VGA - VGA; Signal Cable DVI-D - DVI-D; Monitor; Power Cable; CD-ROM; Sales Office List; User Manual
Safety and Ergonomics	EPEAT Silver™; CE; TCO 5.0; ErP; TÜV Ergonomics; TÜV GS; GEEA/Energy Label; Energy Star 5.0; FCC Class B; PCT/Gost; UL C-UL or CSA; CCC; ISO 9241-307 (pixel failure class I); MPR II/MPR III; RoHS
Warranty	3 years warranty incl. backlight

